

Xerox® Phaser® 4622

Black and White Printer



| Phaser 4622DN | |
|---|--|
| Output Speed | Up to 62 ppm A4 / 210 x 297 mm |
| Automatic Two-sided | Up to 43 ppm A4 / 210 x 297 mm |
| Paper Handling – Input | |
| Multipurpose Tray – Tray 1 | |
| Capacity¹ | 100 sheets |
| Sizes | Custom sizes: 76 x 127 mm to 216 x 356 mm |
| Weights | 60 to 220 gsm |
| Media Types | Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Envelopes Letterhead Hole punched Archive Transparencies Recycled Bond |
| Tray 2 | |
| Capacity¹ | 550 sheets |
| Sizes | Custom sizes: 98.6 x 148.5 mm to 216 x 356 mm |
| Weights | 60 to 163 gsm |
| Media Types | Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Letterhead Hole punched Archive Recycled Bond |
| Up to 4 Additional Trays (Optional) – Only 2 additional trays can be used if the optional High Capacity Feeder is installed | |
| Capacity¹ | 550 sheets each |
| Sizes | Custom sizes: 139.7 x 210 mm to 216 x 356 mm |
| Weights | 60 to 163 gsm |

Xerox® Phaser® 4622

| | |
|--|--|
| Media Types | Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Letterhead Hole punched Archive Recycled Bond |
| High Capacity Feeder – You cannot add a High Capacity Feeder if more than 4 paper trays are being utilised. | |
| Capacity | 2,000 sheets |
| Sizes | A4 |
| Weights | 60 to 90 gsm |
| Media Types | Plain Punched Pre-printed Recycled Bond Archive Letterhead Custom |
| Paper Input Capacity | |
| Standard Paper Capacity¹ | 650 sheets |
| Maximum Paper Capacity¹ | 3,750 sheets |
| Paper Output | |
| Automatic Two-sided Output | 500 sheets |
| Print | |
| First-page-out Time | As fast as 7.8 seconds |
| Print Resolution | Up to 1200 x 1200 dpi |
| Maximum Print Area | 4 mm from all edges or 207.7 mm x 347.4 mm (default) |
| Memory (std / max) | 256 MB / 768 MB optional 320 GB HDD |
| Processor | 600 MHz Dual-core ARM |
| Page Description Languages | PCL® 5e and 6 emulations PostScript® 3™ emulation PDF emulation Epson |
| Connectivity | 10/100/1000Base-T Ethernet, High Speed USB 2.0, Optional Wireless 802.11n with WPA 2 Enterprise |
| Print Features | Booklet printing Scaling Fit to page Watermarks Custom-size pages N-up Secure print Collation Personal print Smart duplex |
| Supported Operating Systems | Microsoft® Windows® XP SP1, Vista, 7, Windows 8, Windows 8.1, 2008 Server, 2003 Server, 2012 Server Mac OS® 10.5 and later Various Linux® and UNIX® distributions, including: <ul style="list-style-type: none"> • IBM® AIX® 5 • HP-UX® 11i v2 • openSUSE® 11 • Red Hat® Fedora® Core 11-14 • Ubuntu® |

| | | | |
|--|--|---|-------------------------|
| Print Drivers | Microsoft Windows XP and above 2003 Server and above Mac OS 10.5 and above Red Hat Enterprise 4, 5 Fedora Core 14-16 openSUSE 11, 12 IBM AIX-5 HP-UX 11, 11i Solaris® 9, 10 Ubuntu Xerox® Global Print Driver® Xerox® Mobile Express Driver® | | |
| Font Capability | 136 PostScript® Fonts; 93 PCL® Fonts | | |
| Xerox® Mobile Express Driver® | <p>Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management | | |
| Xerox® Global Print Driver® | <p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management | | |
| Security | | | |
| Security Features | Secure HTTPS (SSL) IPsec 802.1X Authentication Network Authentication IPv6 SNMPv3 Image Overwrite Audit Log Xerox Secure Access Unified ID System® (optional) IP Filtering Secure Print | | |
| Wi-Fi Security | | | |
| | Authentication Method | Encryption | Productivity Kit |
| | Open WPA PSK WPA PSK / WPA2 PSK | WEP 64 / 128 ASCII / HEX TKIP AES | No |
| | WPA Enterprise WPA Enterprise / WPA 2™ Enterprise WPA Enterprise Authentication Method options: <ul style="list-style-type: none"> • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP | TKIP AES | Yes |
| Device Management | | | |
| Xerox® CentreWare® Web | | | |
| | <ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management | | |
| Xerox® CentreWare® Internet Services – Integrated Device Web Page | | | |
| Device Status | Web server embedded <ul style="list-style-type: none"> • Tray status / contents • Consumables status | | |
| Print Queue Viewing | Complete job print queue management – hold, release, promote and delete | | |

Xerox® Phaser® 4622

| | |
|--------------------------------------|--|
| Job Submission | Print-ready files (PS, PCL®, TIFF, PDF) Output feature selection |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Microsoft® Internet Explorer® 7 Firefox® version 4 and above |
| Xerox® Mobile Solutions | |
| Xerox® PrintBack | PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple® iOS- or Android™-based mobile device. When you're working off-site or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) with uncompromised print quality. |
| Xerox® Mobile Express Driver® | The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver. |
| Apple® AirPrint | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. |

Device Specifications

| | |
|-------------------|--|
| Duty Cycle | |
| | Up to 275,000 pages per month ² |

| | |
|---|---|
| Recommended Monthly Print Volume | |
| | Up to 25,000 pages per month ³ |

| | |
|---|--|
| Power Consumption | |
| 220 to 240 VAC 50 / 60 Hz, 5.0 A | |

| | |
|----------------------------------|---|
| Continuous Printing | 4622V_ADN (52 ppm): 820 watts; 4622V_DN (62 ppm): 900 watts |
| Ready (Standby) Mode | 4622V_ADN (52 ppm): 110 watts; 4622V_DN (62 ppm): 120 watts |
| Energy Saver Mode (Sleep) | 4622V_ADN (52 ppm) and 4622V_DN (62 ppm): 2.8 watts |

Environment

| | |
|---------------------------------------|--|
| Warm-up Time (from Power Save) | First print: As fast as 45 seconds User Interface ready and programmable: 2 seconds |
| Warm-up (from Power On) | 65 seconds User Interface ready and programmable: 54 seconds (max) |
| Temperature Range | 10°-32° C |
| Humidity | 20-85% |

Sound Pressure Levels

| | |
|----------------------------|----------|
| Printing / Copying | 58 dB(A) |
| Standby | 30 dB(A) |
| Quiet Mode Printing | 52 dB(A) |
| Energy Save Mode | 0 dB(A) |

| Dimensions and Weights (Unpackaged) | Width | Depth | Height | Weight |
|--|--------------|--------------|---------------|---------------|
| Phaser 4622 | 476 mm | 541 mm | 420 mm | 34.6 kg |
| 550-sheet Feeder | 464 mm | 521 mm | 148 mm | 13.2 kg |
| High Capacity Feeder | 480 mm | 569 mm | 451 mm | 33 kg |
| Finisher | 410 mm | 444 mm | 424 mm | 7.9 kg |
| Mail Box | 351 mm | 296 mm | 422 mm | 3.6 kg |
| Stand | 480 mm | 553 mm | 84 mm | 17.1 kg |

| Dimensions and Weights (Packaged) | | | | |
|-----------------------------------|--------|--------|--------|---------|
| Phaser 4622 | 627 mm | 698 mm | 685 mm | 40.2 kg |
| 550-sheet Feeder | 656 mm | 715 mm | 334 mm | 13.2 kg |
| High Capacity Feeder | 670 mm | 840 mm | 587 mm | 33 kg |
| Finisher | 595 mm | 484 mm | 453 mm | 11.1 kg |
| Mail Box | 461 mm | 366 mm | 457 mm | 6.3 kg |
| Stand | 682 mm | 609 mm | 290 mm | 17.1 kg |

| Certifications | |
|----------------|--|
| | Listed to UL 60950-1/CSA 60950-1-07+A1:2011, 2nd Edition, FDA/CDRH – Class 1 Laser Product, FCC Part 15, Class A, Canada ICES-003, Class A, CE marked, Low Voltage Directive 2006/95/EC, EN 60950-1, 2nd Edition, EN 60825-1 – Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class A, EN 55024, RoHS Directive 2011/65/EC, WEEE Directive 2002/96/EC, ENERGY STAR qualified, Section 508 Compliant, Blue Angel certified ⁴ , TAA compliant (requires YDN configuration) |
| | To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . |

| What Comes in the Box | |
|-----------------------|---|
| | Phaser 4622 Printer Toner cartridge (13,000 page capacity ⁵) Drum cartridge Quick Installation Guide, Quick Use Guide, Driver CD, Documentation CD (User Manual, System Admin. Guide) Power cable |

| Supplies and Options | Description | Order Number |
|---|---------------------------------|--------------|
| Standard Capacity Toner Cartridge | 13,000 impressions ⁵ | 106R01533 |
| High Capacity Toner Cartridge | 30,000 impressions ⁵ | 106R01535 |
| TTA compliant High Capacity Toner Cartridge | 30,000 impressions ⁵ | 106R02638 |
| Xerox® SmartKit® Drum Cartridge | 80,000 impressions ⁶ | 113R00762 |
| TAA compliant Drum Cartridge | 80,000 impressions ⁶ | 113R00769 |
| Options | | Order Number |
| Hard Drive Kit: 320 GB | | 097N02157 |
| 550-sheet Paper Tray | | 097N01874 |
| 2,000-sheet High Capacity Feeder (includes stand) | | 097N01875 |
| Finisher / Stapler | | 097N01876 |
| 4-bin Mailbox | | 097N01877 |
| Stand | | 097N01916 |
| 512 MB Memory | | 097N01878 |
| Internal Wireless Network Adapter | | 097N01880 |

¹ Paper capacities are based on 75 gsm stock. Capacities will vary with different weight stocks.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

⁴ Phaser 4622V_ADN is the Blue Angel compliant configuration at 52 ppm.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared Yield based on A4 (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

